SPECIFICATION FOR PRECCISION TEST PRESSURE GAUGE (0-600 kg/cm^2)

General:
SS Bourdon types 10" dial PRECISION TEST PRESSURE GAUGE with anti parallax mirror and easy pointer zero adjustment.

Specifications:

- Measuring range : 0 to 600 kg/cm^2.
- Least count : 1 kg/cm^2
- Accuracy class : $\pm$ 0.25%
- Pointer : Knife edge anti parallax mirror.
- Adjustment : Easy Pointer Zero adjustment.
- Movement gears : SS.
- Process Connection : ½" BSP bottom entry.
- Adaptor : To convert process connection to M20x1.5 along with Snubber.
- Zero Stopper : With suitable pin.
- Window : Toughened glass.
- Accessory : Glass removing tool (Two sets for total supply)
- Carry box cushion packed : Suitable wooden carry box with

Calibration: Gauges are to be calibrated at any Govt. recognized lab or NABL accredited lab for minimum 7 points of the range (0,100,200,300,400,500&600 kg/cm^2).Certificate to be enclosed. Price to be quoted inclusive of calibration charges.

PLEASE NOTE:

1. The instrument offered can be better than the above specifications.
2. Should have service facility in India with factory trained engineers to take care of the equipment supplied and to reduce the down time.
3. The product catalogue should contain only the product offered in depth preferably highlighting the model offered.
4. Two sets of original product catalogue to be enclosed with the offer. Without this offer will be rejected totally.
5. Vendor should submit the offer with detailed specification of the product offered. The offers given as **"as per your specifications**" will be rejected.
6. Factory calibration not accepted.